

STONE CLASSIC SYSTEM



CTi's Stone Classic System is a true state of the art coating that resurfaces old and new concrete around the home. It is perfect for areas where you need a tough, but beautiful floor covering. The Stone Classic System will give your home a custom built look for much less than you would pay for marble, granite or other industry standard products.

Stone Classic is a formulation of acrylics and resins that bond with concrete to create a tough surface that resists chipping and staining. Stone Classic retains its rich coloring and good looks for years.

Stone Classic can be used on:

- Fovers
- Dining Room Floors
- Kitchen Floors
- Basements

Outside it can be used on:

- Patios
- Walkways
- Pool Decks
- Driveways

Technical Information (sealed with Series 150 Clear):

Compressive Strength 5715 psi
Tensile Strength 615 psi
Flexural Strength 1585 psi
Sheer Bond Strength 650 psi

Abrasion Resistance 18 in.-lbs after 28 days

Chloride Ion Resistance Ponding 3% Sodium Choride/60 days 100% at

1" depth

Freeze/Thaw Resistance Passes 60 cycles

UV Resistance No discoloration when exposed to Ultra-Violet
Sulfuric Acid 10% solution, 5 min. immersion – unaffected
Sodium Hydroxide 10% solution, 5 min. immersion – unaffected
Citric Acid 10% solution, 5 min. immersion – unaffected
Lactic Acid 10% solution, 5 min. immersion – unaffected
Gasoline 5 minute immersion – abrades slightly

YOUR AUTHORIZED DEALER

8770 133rd Ave. N., Largo, FL 33773 P800.447.6573 or 727.535.4651 F 727.536.8273 designcti.com

Colors are matched as closely as possible to our standards. Colors may be affected by age, light and texture. The color selector is designed to assist you in making your selection from CTi's Acrylistain System colors. CTi's Acrylistain System colors are measured by weight (not volume) and are designed to be mixed with water as the vehicle to dispense the pigments. Colors will vary slightly to dramatically based on application, substrate, temperature and humidity. To ensure proper color, the entire contents of CTi's Acrylistain System should be used. Be sure to thoroughly read all application data. Due to reproduction limitations, it is necessary to reserve the right to allow for reasonable variations of application. Printed colors show approximate colors with the effect of certain texture and sealer alteration along with finishing technique.