

COMMERCIAL COATINGS

Pro Seal 200 - Chemical Resistant Urethane



Super Seal 210 – Epoxy Floor Covering Standard Colors



Other Colors Available



CTI provides a number of solutions for your business and industrial needs. Whether it's providing your company's logo to the entrance to your business or giving your warehouse a chemical resistant floor that can withstand forklift traffic, CTi has the coating that is right for you.

CTi provides a full line of urethane and epoxy floors that can give an automotive service bay, warehouse floor, commercial kitchen or other industrial areas a tough, chemical resistant floor that is easy to clean, dust free and gives the area á sharp, clean look. Our urethane and epoxy floors will also withstand airplane traffic and heavy machinery to keep your work area looking great. In addition, CTi can put your company's logo and other designs to create a look that is one of a kind. Our commercial applications are designed to withstand heavy foot traffic, vehicular traffic and keep its great look for years.

CTI Commercial floors can be used in:

- Warehouses
- Airplane hangars
- Workshops
- Commercial Kitchens
- Animal kennels and shelters

Our commercial sealers can protect our decorative overlays in areas such as:

- Restaurant interiors and entrances
- Hair Salons
- Schools
- Mall and Plaza store fronts

Physical Performance Properties

(Sealed with Pro Seal 200) – Dry Film Hardness – pencil 3H

Taber Abrasion

(mg loss per 1000 cycles, CS-17 sheel, 1000g load) 39.4 Impact resistance, in lbs

Direct	50	Skydrol B-4 Hydraulic Fluid	No effect
Reverse	10	50% Sodium Hydroxide 10% Acetic Acid	No effect
QUV Weatherometer		30% NH3OH Gasoline	No effect
Oxidation	No effect	Xylene	No effect
Loss of gloss	No effect	50% Sulfuric	No effect
Blistering	No effect	25% Nitric Acid	No effect
Yellowing	No effect	37% Hydrochloric Acid	No effect

YOUR AUTHORIZED DEALER

8770 133rd Ave. N., Largo, FL 33773 P800.447.6573 or 727.535.4651 F 727.536.8273 designcti.com

Colors are matched as closely as possible to our standards. Colors may be affected by age, light and texture. The color selector is designed to assist you in making your selection from CTi's Acrylistain System colors. CTi's Acrylistain System colors are measured by weight (not volume) and are designed to be mixed with water as the vehicle to dispense the pigments. Colors will vary slightly to dramatically based on application, substrate, temperature and humidity. To ensure proper color, the entire contents of CTi's Acrylistain System should be used. Be sure to thoroughly read all application data. Due to reproduction limitations, it is necessary to reserve the right to allow for reasonable variations of application. Printed colors show approximate colors with the effect of certain texture and sealer alteration along with finishing technique.